

FMM600 动力电缆 Motor cables



- PVC外护套
- 阻燃
- 抗UV
- 耐油
- PVC outer jacket
- Flame resistance
- UV-resistance
- Oil-resistant

移动参数 Dynamic Information

	最小弯曲半径 Min. bending radius	拖链内移动 Moving in cable carriers	7.5 x d
		非拖链内移动 Flexible moving	6 x d
		固定铺设 Fixed installation	4 x d
	使用温度范围 Temperature	拖链内移动 Moving in cable carriers	+5°C至to +70°C
		非拖链内移动 Flexible moving	-5°C至to +70°C
		固定铺设 Fixed installation	-15°C至to +70°C
	最大速度 v max.	架空 Unsupported	10 m/s
		滑行 Gliding	5 m/s
	最大加速度 a max.	80 m/s ²	
	行程距离 Travel distance	架空应用和行程距离小于100米的滑行应用 Unsupported travels and up to 100 m for gliding applications	
	可扭转 Torsion	±90°/m	

电缆结构 Cable structure

	导体 Conductor	截面积Cross-sectional < 10 mm ² : 高抗弯强度的精细裸铜多股线 (符合 EN 60228 标准) Stranded conductor in especially bending-resistant version consisting of bare copper wires (according to DIN EN 60228).
		截面积Cross-sectional ≥ 10 mm ² : 细铜丝先编织成束然后绞在一起 (符合 EN 60228 标准) Conductor cable consisting of pre-leads(according to DIN EN 60228).
	绝缘材料 Conductor insulation	高机械性能、低电容的XLPE混合物 Mechanically high-quality, especially low-capacitance XLPE mixture.
	芯线结构 Conductor construction	芯线以短节距绕高抗拉中心线绞合在一起 Cores wound with a short pitch length around a high tensile strength centre element.
	芯线识别 Color code	一根为黄绿线, 其余均为黑色芯线带白色数字Black cores with white numbers, one green-yellow core. 芯线Core1: U/L1/C/L+ 芯线Core2: V/L2 芯线Core3: W/L3/D/L- 芯线Core4: 4/N
	外护套 Outer jacket	低粘性、耐油的PVC基混合物, 符合拖链要求 Low adhesion mixture on the basis of PVC, adapted to suit the requirements in cable carriers. 颜色: 黑色 Color: Black RAL 9005

FLEXMOV® Motor cables

FLEXMOV® 动力电缆

电气参数 Electrical Information

	额定电压 Nominal voltage	U ₀ /U: 600/1000 V (符合following VDE0298-3)
	测试电压 Test voltage	4000 V (符合following EN50395)

特性和认证 Properties and approvals

	抗紫外线 UV-resistance	中等 Medium
	耐油性 Oil resistance	耐油 (符合 IEC60811-404 标准, 经SGS检测), 耐生物油 (符合VDMA24568 标准, 经SGS检测) Oil-resistant (following IEC60811-404, tested by SGS), bio-oil-resistant (following VDMA24568, tested by SGS)
	阻燃 Flame resistance	符合According to IEC 60332-1-2、VW-1、FT1
	REACH	符合 Accordding to the regulation (EC) No. 1907/2006 (REACH)
	EAC	经认证Certificate No. KG 417/043.CN.02.00249
	无铅 Lead-free	符合Following 2015/863/EU (RoHS-II 经SGS检测 Tested by SGS)
	无尘室 Cleanroom	符合Following ISO 14644-1
	CE	符合Following 2014/35/EU
	UL	符合Following UL2570, 1000V, 80°C

质保使用寿命 Guaranteed service life

往返行程 Double strokes	500万次 5 million times	750万次 7.5 million times	1000万次 10 million times
适用温度范围 Temperature, from/to [°C]	最小弯曲半径 R min. [系数factor x d]	最小弯曲半径 R min. [系数factor x d]	最小弯曲半径 R min. [系数factor x d]
+5/+15	10	11	12
+15/+60	7.5	8.5	9.5
+60/+70	10	11	12

FMM600

FLEXMOV®

www.csb-ep.com
sales@csb-ep.com

电话: 0573 84186133/84185527
Tel: 0086 573 84187009

FMM600 动力电缆 Motor cables

产品编码 Part No.	芯数及截面积 Number of cores and conductor nominal cross-section [mm]	外径 Outer diameter [mm]	铜含量 Copper index [kg/km]	重量 Weight [kg/km]
FMM600.15.04	4G1.5	8	61	104
FMM600.25.04	4G2.5	10	100	166
FMM600.25.05	5G2.5	11	124	203
FMM600.40.04	4G4.0	11.5	163	249
FMM600.40.05	5G4.0	12.5	204	302
FMM600.60.04	4G6.0	13.5	237	343
FMM600.60.05	5G6.0	15	297	410
FMM600.100.04	4G10	16.5	407	548
FMM600.100.05	5G10	19.5	515	684
FMM600.160.04	4G16	20	646	826
FMM600.160.05	5G16	23.5	815	1067
FMM600.250.04	4G25	25	1014	1320
FMM600.350.04	4G35	28.5	1439	1795

注Note: 外径是指参考值 The outer diameters are reference values.

G: 带黄-绿接地线 With green-yellow earth core

x: 不带接地线 Without earth core